

Importers and Distributors of CCTV products

## 20M IR Indoor IP Colour Camera

### CIP20D



#### Features

Indoor IR Network camera

Hi-Res. – 3MP

IR LED:  $\phi$  5x24 Pcs IR LED, working distance: 20M

Built-in POE

H.264 Dual stream, Full Real Time

Lens: Board Lens 3.6

#### Specifications

TV System	PAL/NTSC
Electronic Shutter Time	Auto: PAL 1/1-1/10000Sec; NTSC 1/1-1/10000Sec
Sync System	External
Usable Illumination	0.01Lux
S/N Ratio	$\geq$ 52dB
Scanning System	Progressive
Video Output	Network
<b>Lens</b>	
Focus Length	3.6mm
Pixels	3 Mega Pixel
<b>Night Vision</b>	
Infrared Distance	20M
IR Status	Under 10 Lux By CDS
IR Power On	CDS Auto Control
<b>Network</b>	
Ethernet	RJ-45 (10/100Base-T)
Protocol	IPv4, HTTP, TCP/IP, FTP, NTP, RTSP, UDP, SMTP, DNS, DDNS
ONVIF	Support ONVIF 2.4
P2P	YES, Support QR Code
POE	Optional, Support IEEE 802.3af
WIFI	N/A
Video Delay	0.3S (Within the Lan)
Main Stream	2048 x 1536 pixels
Sub Stream	704*576
	352*288
IE Brower	IE6-11
Smart Phone	iPhone, iPad, Android, Android Pad
<b>Camera Features</b>	
Day/Night	Color/ B&W (IR-CUT )
Compression	H.264/JPEG, Supports recording AVI format.
Image Config	Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, BLC, FLK(Flicker Control)
Motion Detection	Support
Privacy Masking	3 Rectangular Zone
DWDR	YES
Recording Mode	NVR/NAS/CMS/Web
<b>General</b>	
Housing	Metal
IR Cut Filter	YES
Operation Temperature	-10 $^{\circ}$ C ~ +50 $^{\circ}$ C RH95% Max
Storage Temperature	- 20 $^{\circ}$ C ~ +60 $^{\circ}$ C RH95% Max
Power Source	DC12V $\pm$ 10%, 1000mA
Dimension	$\phi$ 86 x 90(H) mm
Weight (POE)	0.2KG
Weight	0.5KG