

*Importers and Distributors of CCTV products*

## 30M IR Indoor IP Colour Camera

### CIP30D1.3MP



#### Features

Indoor IR Network camera

Hi-Res. – 1.3MP

IR LED:  $\phi$  5x36 Pcs IR LED, working distance: 30M

Built-in POE

H.264 Dual stream, Full Real Time

Lens: Board Lens 2.8-12mm

#### Specifications

System Structure	Embedded LINUX RTOS ,dual core 32 bits DSP (TI Davinci DM365) Pure hardware compression, watchdog, 32M Flash, 128M DDR2.	
Image Sensor	1.3 MP CMOS Image sensor.	
Lens Mount	2.8-12mm 4 -9mm optional	
Minimum Illumination	0.1Lux@F1.2, B&W 0.01 Lux@F1.2;	
Photoresistance Linkage	Support linkage between photoresistance input sign, image, IR-Cut and IR lamp. 1 photoresistance	
Day & Night	IR cut filter with auto switch, IR sensor. 1 IR lamp control interface algorithm control IR lamp open and	
Video compression	H.264 compression ,dual stream ( 0.1M-6Mbps adjustable)	
Image Output	Main Stream: 1280×960,1024×768,1280×720	
	Sub Stream: 960×540,640×360,480×270,352×288,320×240,352×192,320×192,288×192,256×192	
Analog Output	1 analog video output ,CVBS supported, PAL/NTSC (configurable)	
Audio Interface	1 CH audio input (Level: 2Vp-p, Impedance: 1k $\Omega$ ) , sound pickup supported	
	1 CH audio output (Impedance:16 $\Omega$ ,power output : 30mw), headphone connection or amplifier	
Audio Process	AAC or G711 codec standard, two-way voice talkback, audio and video synchronization.	
Storage Function	1 USB interface ( Max: 64G) , front storage supported,3G or WIFI extend supported	
	1 TF/SD storage extend interface (Remarks: need SD storage card plug)	
Alarm Interface	1 CH switch input , alarm input ,recording and background linkage supported	
	1CH switch output, sound and light alarm supported.	
Alarm Function	Motion detection and IO alarm linkage ip camera storage supported	
	Center warning and picture pop-up linkage supported ( after motion detection and IO alarm)	
Network Interface	1 RS422/ RS485 interface, PELCO and other PTZ protocols are available	
	1RJ45 Ethernet interface, 10/100M adaptation	
Network Function	WEB configure and OSD supported, real time recording, transmission and playback, download.	
	Free UC2 client software supported, VM6000 platform supported, SDK for customer software	
Other	Product dimension	119*98mm
	Net :Weight	0.85KG
	Voltage	DC12V
	Consumption	3W