

*Importers and Distributors of CCTV products*

## Megapixel IR Dome Network Camera

### CIP328



#### Features

POE (Power over Ethernet)

IR LED: 12 Pcs IR LED, working distance: 10M

HD – 1.3 Mega Pixel

3 Axis mechanism for easy adjustment

ONVIF standard to simplify integration

Lens: Board Lens 3.8mm/F1.5

External Alarm I/O device connection

#### Specifications

<b>Network</b>	Network Compression	H.264 / MPEG4 / MJPEG	
	LAN Port	Yes	
	LAN Speed	10/100 Based-T Ethernet	
	Supported Protocols	DDNS, PPPoE, DHCP, NTP, SNTP, TCP/IP, ICMP, SMTP, FTP, HTTP, RTP, RTSP, RTCP, IPv4, Bonjour, UPnP, DNS, UDP, IGMP, QoS	
	ONVIF Compatible	Yes	
	Frame Rate	PAL – 25, NTSC – 30, FPS	
	Number of Online Users	10	
	Security	Multiple user access levels with passwords	
		IP address filtering	
		Digest Authentication	
Remote Access	Internet Explorer on Windows operating system		
	EagleEyes on iPhone, iPad & Android devices		
<b>Camera</b>	Image Sensor	¼" SONY HR image sensor	
	Video Resolution	SXGA, 720P, VGA, QVGA	
	Minimum Illumination	0.1 Lux / F1.5, 0 Lux with LEDs on	
	S/N Ratio	More than 48dB (AGC off)	
	Lens	f3.8mm / F1.5 (Viewing Angle 53.7° Horizontal, 34.1° Vertical)	
	PIR Sensor	Detection range 76° angle up to 5M distance at 2.5M height	
	Power Supply (±10%)	12VDC / 1A	
	Operating Temperature	0°C ~ 40°C	
<b>Other</b>	Motion Detection	Yes	
	Event Notification	FTP / Email / SMS	
	Digital Pan / Tilt and Zoom	Yes	



**South Africa 082 461 5983**  
**U.K. 07081 825 466**

*Importers and Distributors of CCTV products*