

## H.265 16 Channel 4K NVR

### NVR 6032C

#### Front Panel :



#### Back Panel :



#### Features

- Support H.265+/H.265/H.264 coding front end adaptive access.
- Support ONVIF, Highprofile S, Highprofile G, and can be connected to network cameras that comply with ONVIF, RTSP standards made by many major manufacturers.
- Support IPC front-end Intelligence: target count, object left/lost, area detection, line crossing.
- Support AEeye P2P cloud services, through cloud access, cloud monitoring, cloud forwarding to achieve any terminal access to NVR anytime, anywhere.
- Support immediate playback function under preview screen without affecting other channel preview.
- Support for adaptive bit stream preview and playback 4 screen maximum support 1280\*720, single screen 3840\*2160.
- Provide networked centralized monitoring and management software.

#### Software interface:



<b>Product Model</b>		<b>NVR-6032C</b>
Operating System		Embedded LINUX operating system
Video Standard		H.265+/ H.265/H.264
Intelligent Support	NVR support	Target count, object left/lost, area detection, line crossing
	IPC support	Various intelligent detection access and linkages such as line crossing, wondering, face, license plate, audio input abnormality, virtual focus and scene change.
Video & Audio Input	Video Input	32CH 5MP, 25CH 5MP, 16CH 4K H.265+/H.265/H.264 IP Camera
	Bandwidth	80M
	Audio Input	IPC composite stream network audio input
Video & Audio Output	HDMI Output	1CH, Resolution: 4K(3840×2160)/30Hz, 1920×1080/60Hz, 1600×1200/60Hz, 1280×1024/60Hz, 1280×720/60Hz, 1024×768/60Hz
	VGA Output	1CH, Resolution: 1920×1080/60Hz, 1280×1024/60Hz, 1280×720/60Hz, 1024×768/60Hz
	Audio Output	1CH, RCA port (Linear level, impedance: 1KΩ)
	Preview Split	1/4//9/16 screen
Video & Audio Coding	Video Resolution	8MP/5MP/4MP/3MP/1080P and below resolution
	Synchronized Playback	16ch /9ch /4ch Synchronized Playback (Different in various access modes)
	Network Port	1 x RJ45 10M/100M adaptive Ethernet port
	USB Port	Front 1x USB2.0; Rear 1x USB2.0
HDD	HDD Port	2x SATA
	MAX Capacity	Each port up to 8TB
Network Management	Network Protocol	UPnP (Plug & Play), SNMP (Simple Network Management), NTP (Network Timekeeping), SADP (Device Network Search), SMTP (Mail Service), NFS (Access NAS), iSCSI (IP SAN Application), PPPoE (Dial-up Internet access), DHCP (automatically obtain IP address)
P2P Remote Monitoring	AEeye	Supports iPhone, iPad, Android Smart phone
		Supports Windows 7 and above computer client, supports Apple MAC computer client
Power Supply		DC 12V3A (external adapter)
Working Temperature		-10°C-- + 55°C
Working Humidity		10%-90%
Power Consumption		≤15W (without HDD)
Dimensions		Device: 350mm×240mm×68mm, Packing: 409mm×365mm×129mm
Weight (Without HDD)		N.W.: 1.3Kg; Packing: 2Kg
Outside Carton		5 pcs/carton. Dimension: 675mm×425mm×385mm; Packing: 12Kg
Installation Method		Desktop installation