

Importers and Distributors of CCTV products

30x 3MP I.P. Speed Dome Camera

CIP3MP30X	
	Key Features:
	High Definition – 3 Mega-Pixel
	PWM function, intelligent IR illumination & power consumption is variable, dependent on the zoom factor;
	IR distance 150-280M
	H.264 compression
	7" Total Metal body construction, IP66 rate protection
	Smart movable LED board , IR LED angle variable dependent on the zoom factor;
Specifications	
Sensor	1/3" progressive CMOS HiSilicon sensor
Total pixel	3.0 Megapixels
Lens	30X zoom lens
Iris	F1.6~F4.8
Min.illumination	Color:0.05Lux B/W:0.01Lux
D/N	IR Cut
WB	Manual/Auto
AGC	Manual/Auto
S/N Ratio	≥50dB
Communications Protocol	TCP/IP, HTTP, NTP,IGMP,DHCP,UDP,SMTP,RTP,RTSP,ARP,DDNS,DNS,PPPoE,P2P
Software Control	IE, CMS, Management Platform
Mobile View(optional)	Android , iPhone
Horizontal Rotation Range	360°
Tilt Rotation Range	93°
Auto Flip	Horizontal 180°, Vertical 93°
Horizontal Rotation Speed	0.02 ~ 450°/s
Tilt Rotation Speed	0.02 ~ 160°/s
Ratio Speed	Supports
Preset Points	220
Go to Preset Speed	1-64 grades available
360° Scan	1-64 grades setting available
A-B Scan	User programmable
A-B Scan Speed	1-64 grades setting available

Importers and Distributors of CCTV products

Dwell Preset	1-60s interval available
Guard Tours	8 groups
Guard Points	Max.16 points, dwell time user selectable (Nov.)
Pattern Scan	4 pcs
Pattern Scan Record	Max.512 commands
Time Scheduling Function	6 tasks
PWR On Action	Memory/Pattern 1/Tour 1/360° scan/A-B scan/Park 1/None
Park Mode	Pattern 1/Tour 1/360° scan/A-B scan/Park 1/None
Park Time	1-60mins setting available
Menu	Multiple Languages: English, Spanish, French, German, Italian etc. on IE interface
Pan and Tilt position display	Support
Communication Protocol	Pelco-D, Pelco-P
Baud Rate	1200/2400/4800/9600bps (Default is 9600bps)
Operating Temperature	Indoor: 0°~ +40° Outdoor: -40°~ +60°
Operating Humidity	≤95% Non Condensing
Power Supply	DC12V 4A / AC24V 3A
Lightning Protection	Transient voltage 6000V
Wiper	No
IR parameters	
Auto Control IR LED	PWM
LEDs	Array 42Mil *10pcs
IR distance	Up to 150m-280m
IR illumination on	1-15 grades selectable
Support ambient light detection	1-50 grades selectable