

*Importers and Distributors of CCTV products*

## 4 in 1 IR High Speed Dome 20X, 2MP

CSD2MP20X		
		<b>Key Features:</b>
PTZ Control via coax		
8pcs High quality array LEDs, auto-switch to long/middle/close distance focus, 80M IR distance		
360° continuous rotation, no monitoring blind area		
Horizontal Rotation Speed 0.1°~100°/s, Vertical rotation speed 0.1° ~ 100°/s.		
255 presets, the positioning accuracy of 0.5 degrees		
Support: Guard position/Power up Action /Park action/3 groups Tours /Pattern/Area scanning/360° horizontal scanning.		
Full metal aluminum die-casting, all-weather environment design, high and low temperature resistant, waterproof to IP66		
Camera	sensor	1/2.8" CMOS
	Definition	2. 0M pixels 1920 (H) X 1080 (V)
	Video System	PAL/NTSC
	Minimum	colour : 0.1Lux B/W : 0.01Lux
	Video output	AHD-H(1Vp-p 75Ω)
	noise-signal ratio	≥50DB
Lens	lens	4.7 to 94mm (F1.6 to F2.7) 20X Optical zoom
Function	IR control	Depending on the focal length
	IR distance	80m
	Rotation range	Vertical : 0°~360° ; Horizontal : -15°~90°
	Rotational speed	Keying: Vertical : 0°~100°/s ; Horizontal : 0°~100°/s
	Presets	255
	Cruise scan	4 ( Each set of 10 preset positions, the residence time can be adjusted
	Area scanning	Support
	Horizontal scanning	Support
	Park action	Preset / Area scanning / Horizontal scanning / Cruise scan
INPUT/OUTPUT	Analog video output	1.0Vpp/75Ω, NTSC or PAL, BNC Interface
	control interface	Support: 1. Coaxial control 2. RS485
General specification	Power	DC12V-2A, Power Consumption <18W
	work environment	temperature -20~60°C ; humidity <90%
	Protection level	IP66, 4000V Lightning protection, surge protection and surge protection
	material quality	Metal aluminium
	GW	2.35kg (single package)