

Importers and Distributors of CCTV products

30 x I.R. Speed Dome Camera

CSDIR30X	
	Key Features:
	PWM function, intelligent IR illumination & power consumption is variable, dependent on the zoom factor;
	IR distance 100 M. I.R. output automatically varies with zoom factor
	30 times optical zoom
	Dome ID, baud rate, communication protocol can be set via the controller;
	Supported Protocols : Pelco-D/P
	6" metal body construction, waterproof IP 66;
	Array type I.R. light source for extended life.
Specifications	
Image sensor	1/4"SONY Exview HAD CCD,30 magnification
TV Lines	480 TV Lines (colour) 600 TV Lines (B/W)
PTZ communication	RS485
PTZ protocol	PELCO-P 、 PELCO-D
BitRate	1200bps/2400bps/4800bps/9600bps automatic identification
Horizontal rotate speed	200°/s
Vertical rotate speed	100°/s
Auto flip	Horizontal 180°, Vertical 180°
IR Control	Auto / Manual / Key
IR Leds auto control	Auto (Turn on or off the IR LEDs according to the need)
Horizontal scanning speed	1-64 levels adjustable
Preset points	220 points
Dwell preset	01-64 levels adjustable
Patrol groups	3 group (16 preset points)
Go to Preset speed	01-64 selectable points
Dome ID	Select in menu: 001-250
Voltage	AC/DC 12V
Power Consumption	Maximum (36 W at night/ 6W at daytime)
Lightning Protection	Transient voltage 6000V
Working Temp.	-40° ~ 60°
Maximum Operating Humidity	95% Non Condensing