


*Importers and Distributors of CCTV products*

## 20 x I.R. 2MP I.P. Speed Dome Camera

### CIP2SDIR20W-2.1

	<p><b>Key Features:</b></p> <p>SONY high performance 1/2.8" 2MP CMOS sensor</p> <p>Supports Onvif 2.4.</p> <p>Using imported dot matrix large glass lamps and imported high-speed glass lamp light, to ensure the IR distance 100-120 m; product life can reach 30,000 hours.</p> <p>Intelligent infrared control technology automatically controls the infrared light according to the environment. Under the premise of ensuring monitoring results, it can effectively enhance the infrared lamp's life and ensure the product stability.</p> <p>Constant current circuit design ensures stable operation of the infrared light. And it won't reduce the infrared lamps' life caused by fluctuations of the power supply.</p>
---	--

### Specifications

Image sensor	1/2.8"SONY CMOS		
Effective pixel	1980(H)x1080(V)	Horizontal resolution	1080P
S/N ratio	>60dB		
Backlight compensation	On/off		
White balance	Auto		
Electronic shutter	PAL:1/25 ~ 1/100000s NTSC:1/30 ~ 1/100000s		
Focus length	5-90mm		
Optical focus	20x		
Focus system	Auto/Manual/Auto zoom		
IR distance	100-120m		
IR light control and angle	Infrared zoom matching technology		
IR on	Auto/Camera/Timing		
Horizontal range	360°Continuous rotation		
Vertical range	-10~90°		
Preset call speed	Max 200°/S		
Manual call speed	0.01°~180°/S		
Presets	256		
Cruise track	8 groups, each group for 32 presets		
Patrol track	4 groups, each group record 500 actions		
Video compression	H.264 Main Profile encoding ; MJPEG / JPEG Baseline encoding		
Primary stream	1980 * 1080 , 25fps		
Secondary stream	640 * 480 , 25fps		
Video bit rate	32Kbps-16Mbps continuously adjustable,		
Network protocol	TCP/IP、UDP、RTP、RTSP、RTCP、HTTP、DNS、		
ONVIF support	Support		
Protection level	IP66		
Power supply	DC12V(5A)		
Power	35W		
Work temperature	-35-65°C		