


10 x I.R. Indoor Speed Dome Camera

CSDIR10XI	
	<p>Key Features:</p>
	PWM function, intelligent IR illumination & power consumption is variable, dependent on the zoom factor;
	IR distance 50M; Multiple languages for OSD menu
	Support ambient light detection, IR Illumination On 1-15 grade selectable;
	Dome ID, baud rate, communication protocol can be set via the on screen display
	Supported Protocols : Pelco-D/P; Others on special request;
	Park Action includes Home position, 360° scan/A-B scan/cruise 1-3
	Optional IP module (built in provision);
Specifications	
Image Sensor	10 X Sony Effio-E 600 TVL Colour Day/Night CCD
Horizontal Rotation Speed	0.1 - 50°/s
Horizontal Rotation Range	360°
Tilt Rotation Range	94°
Auto Flip	Horizontal 180°, Vertical 90°
Auto control IR LED	PWM
A-B Scan	User programmable
A-B Scan Speed	1-64 speed setting available
Dwell Preset	5 – 60s interval
Preset Points	128
Go to Preset Speed	50°/s
Guard Tours	3 groups
Guard Points	Max.16 points, dwell time user selectable
Park Action	Home position, 360°scan/A-B scan/guard tour 1-3
Park Time	1 – 60 mins
Communication Protocol	Pelco-D, Pelco-P
Communication	RS485
Baud Rate	1200/2400/4800/9600bps
Privacy Mask	8-24pcs (according to zoom module type)
IR Illumination Distance	50M
Operating Temperature	-40°~ +65°
Operating humidity	≤95% Non Condensing
Power	DC 12V ≤3A
Lightning protection	Transient voltage 3000V